



## NS-7570

### BIS-QUAT CORROSION INHIBITOR

**NS-7570** is a water soluble, quaternized, organic corrosion inhibitor for controlling corrosion in a variety of corrosive environments, such as producing wells, flow lines, and saltwater disposal systems. It also possesses excellent anti-foulant properties. **NS-7570** is recommended for continuous injection or slug treatments. Usage rates may vary from 500 ppm in slug treatments to 10 to 50 ppm in continuous treatments. This product is excellent for cleaning and corrosion protection in iron sulfide environments.

**Flammable Liquid**

### Physical Properties:

Chemical Description	Bis-Quat
Physical State @ 77°F	Liquid
pH	8 to 9.5
Pour Point, °F	-4
Flash Point, °F	54
Specific Gravity @ 77°F	0.89 to 0.91
Lbs./Gallon	7.40 to 7.57
Activity	70%

### Solubility:

Soluble  
Water

Non Soluble  
Heavy Aromatic Naphtha  
Kerosene

No warranty expressed or implied of merchantability, fitness for a particular purpose or otherwise is made. Buyers assume all risk of use, storage and hauling. NovaStar LP will not be liable for any incidental or consequential damages arising directly or indirectly concerning the purchase, use, storage, or handling of this product. 0909